

CORONA TRE 150

Il corpo conico, la spirale ed il design del segmento rendono unica questa corona diamantata e insuperabile a livello di prestazioni. Al top della gamma, è l'ideale per gli utenti professionali che non accettano compromessi: taglia tutto, ferro compreso, ad una velocità mai provata prima. Il corpo conico diminuisce gli attriti laterali e aumenta la velocità della foratura, coadiuvato dalla spirale che scarica il materiale d'asporto ed evita i bloccaggi della corona. **Il design e la composizione del segmento diamantato sono stati sviluppati per il carotaggio del cemento armato a secco.**


The conical body, spiral and segmented design make this diamond core bit unique and unbeatable in its performance. At the top of the range, it is ideal for professional users who do not accept compromises. It cuts everything, iron included at a never before seen speed. The conical body reduces the lateral friction and increases perforation speed, assisted by the spiral it removes excess material and avoids blockage of the bit. The design and composition of the diamond segments have been developed for the dry drilling of reinforced concrete.




ACCIAIO SPIRALATO



PER USO
A SECCO



ATTACCO
M16 F



LUNGHEZZA
150 MM

TABELLA TECNICA Technical Spec

cemento stagionato, laterizi, tegole, calcestruzzo armato
concrete, bricks, roof tiles, reinforced concrete



SUPER



OTTIMO

graniti, pietre naturali, porfidi, refrattari
granites, natural stone, porphyries, refractory



BUONO



MEDIO

arenaria, piastre ghiaino, monocottura, bicottura, cemento fresco, asfalto
sandstone, aggregated concrete, single fired tiles, double fired tiles, green concrete, asphalt



SUFFICIENTE

marmi, gres porcellanato, klinker
marble, porcelain tiles, klinker

INADATTO

COD.	Ø	SEGMENTI Segments	RPM
CLS15032M16	32	3	1500-2200
CLS15037M16	37	3	1500-2200
CLS15042M16	42	4	1500-2200
CLS15052M16	52	4	1300-2000
CLS15057M16	57	4	1300-2000
CLS15062M16	62	4	1300-2000
CLS15068M16	68	4	1100-1600
CLS15072M16	72	4	1100-1600
CLS15082M16	82	4	900-1500
CLS15092M16	92	5	800-1300
CLS15102M16	102	5	700-1200
CLS15107M16	107	5	650-1150
CLS15112M16	112	6	650-1150
CLS15122M16	122	6	500-1000
CLS15127M16	127	6	500-1000
CLS15132M16	132	7	500-1000

COD.	Ø	SEGMENTI Segments	RPM
CLS15142M16	142	7	500-800
CLS15152M16	152	7	450-750
CLS15162M16	162	8	450-750
CLS15182M16	182	9	400-700
CLS15205M16	205	9	350-600
CLS15225M16	225	10	350-600
CLS15250M16	250	10	350-600