

MOLA A BATTENTARE ASFALTO

Disco diamantato con spessore maggiorato del segmento, studiato per il taglio di tracce per il posizionamento di cavi elettrici, fibra ottica, circuiti elettrici ecc. Possono essere utilizzati anche in applicazioni di apertura, recupero o allargamento di giunti di dilatazione già esistenti. Idoneo all'utilizzo su macchine taglia suolo con potenze uguali o superiori a 13 hp.

Disponibili dallo spessore 6 allo spessore 20 in vari diametri.

Diamond blade with increased segment thickness, designed for cutting chases to lay electrical cables, fiber optics, electrical circuits, etc. They can also be used for opening, restoring, or widening existing expansion joints. Suitable for use on floor saws with power ratings equal to or greater than 13 hp. Available in thicknesses from 6 to 20 in various diameters.



Ø E SPESSORI A RICHIESTA



TABELLA TECNICA

asfalto



SUPER

calcestruzzo



OTTIMO



BUONO



MEDIO



SUFFICIENTE

INADATTO

COD.	Ø	FORO	SPESSORE
MBA300S06F25	300	25,4 + PIN	6
MBA300S08F25	300	25,4 + PIN	8
MBA300S10F25	300	25,4 + PIN	10
MBA300S12F25	300	25,4 + PIN	12
MBA300S15F25	300	25,4 + PIN	15
MBA350S06F25	350	25,4 + PIN	6
MBA350S08F25	350	25,4 + PIN	8
MBA350S10F25	350	25,4 + PIN	10
MBA350S12F25	350	25,4 + PIN	12
MBA350S15F25	350	25,4 + PIN	15
MBA400S06F25	400	25,4 + PIN	6
MBA400S08F25	400	25,4 + PIN	8
MBA400S10F25	400	25,4 + PIN	10
MBA400S12F25	400	25,4 + PIN	12
MBA400S15F25	400	25,4 + PIN	15
MBA450S06F25	450	25,4 + PIN	6
MBA450S08F25	450	25,4 + PIN	8
MBA450S10F25	450	25,4 + PIN	10
MBA450S12F25	450	25,4 + PIN	12
MBA450S15F25	450	25,4 + PIN	15

* forature a richiesta - boring on request

MOLA A BATTENTARE ASFALTO

[illegible]

* forature a richiesta - boring on request