

MOTORE SSR38

Il MOTORE SSR38 è un motore per carotatrici diamantate adatto per un utilizzo su colonna e per eseguire fori su materiali quali roccia, calcestruzzo, asfalto e muratura. Il motore è dotato di un rubinetto sferico che permette attraverso l'emissione di acqua, sia il raffreddamento del motore stesso sia la rimozione dei fanghi di risulta. Il motore è dotato di 3 velocità meccaniche. Per ogni velocità meccanica, sono disponibili 6 velocità elettroniche selezionabili attraverso i pulsanti sul quadro di comando. Ciò consente all'utilizzatore di effettuare il carotaggio con il numero di giri adeguato al diametro del foro.

MOTOR SSR38 is a motor for diamond core drilling machines suitable for the use on stand drills and to drill materials like rock, concrete, asphalt, masonry. This motor is fitted with a spherical water tap which allows, through the water emission, both the cooling of the motor itself and the removal of excess sludge. Motor SSR38 is fitted with 3 mechanical speeds. For each mechanical speed, 6 electronic speeds are available and they can be selected through the buttons on the control panel. This allows the user to drill with the appropriate number of revolutions, right for the diameter of the hole.



TABELLA TECNICA *Technical Spec*

 Tensione nominale: 230 V <i>Nominal voltage: 230 V</i>	 Numero di giri a pieno (1/min) Livello motore 1: 180-220-260-320-380-440 Livello motore 2: 360-430-520-630-755-880 Livello motore 3: 560-670-810-980-1180-1370 <i>Speed (full load) (1/min):</i> <i>Gear Step1: 180-220-260-320-380-440</i> <i>Gear Step2: 360-430-520-630-755-880</i> <i>Gear Step3: 560-670-810-980-1180-1370</i>
 Corrente nominale: 16 A <i>Nominal current: 16 A</i>	
 Potenza nominale: 3700 W <i>Nominal power: 3700 W</i>	
 Potenza utile: 2700 W <i>Power output: 2700 W</i>	 Ø perforazione su calcestruzzo (mm): 40 - 400 <i>Drill Ø concrete (mm): 40-400</i>
 Frequenza nominale: 50-60 Hz <i>Nominal frequency: 50-60 Hz</i>	 Velocità: 6 elettroniche e 3 manuali. <i>Speed: 6 electronic and 3 mechanical sp.</i> Vel.Tot: 18 <i>Tot.Speeds: 18</i>
 Attacco: 1"1/4 UNC <i>Fitting: 1" 1/4 UNC</i>	 Peso: 18 Kg <i>Weight: 18 Kg</i>

[illegible]